



BP - 900K II

Vertical-insert 24-Pin passbook printer

BP-900KII Vertical-insert 24-Pin passbook printer



BP-900KII Specification

Print type	24-pin impact dot matrix
Print direction	Bi-directional with logic seeking
Print Width(10CPI)	94 Columns / 238.76mm
Print speed(10CPI)	420 CPS (Super high speed) 350 CPS (High speed) 175 CPS (Normal)
Print head Life:	500 million strokes/wire
Resolution	360×360 DPI(Maximum)
Character sets	17 international character sets
Fonts	Draft, Roman, Sans Serif, Courier, Prestige, Script, OCR-A, OCR-B, Orator
Character pitch	10CPI, 12CPI, 15CPI, proportional
Line space	1/6 inch, 1/8 inch, programmable in 1/360 inch increments
Emulation	EPSON ESC/PK2, IBM 2391, OKI5530SC, Olivetti PR40/PR50/PR2
Interface	Standard:[USB2.0][Parallel][Serial] Options:[additional USB2.0][additional Serial][Ethernet]
Buffer Memory	132KB
Ribbon	Model:JMR128, Life(draft mode):> 8 million characters Model:JMR131, Life(draft mode):> 12 million characters
Noise	<55dB(A)(ISO7779 standard)
Paper feed type	Cut sheet: front in, front out, front in, rear out Tractor paper: rear in, front out
Paper specification	Cut sheet: Width: 60~245 mm Continuous paper: Width: 60~245 mm Passbook Width: 100~245 mm
Max paper thickness	2.8mm
Copy	Original+6 copies
Function	Automatic document border detection Automatic paper thickness detection Automatic skew adjust Automatic Pin Break Compensation, Automatic Pin Rotation Replacement, Automatic Emulation Match, Online Parameter Setting, LCD Display
Dimension (W×D×H)	397mm × 287.5mm × 195mm
Weight	Approx. 8.3Kg
Optional part	Double-side scanning module, tractor, MSR (magnetic stripe reader)
Environmental conditions	Operating:Temperature: 5~35 C , Humidity: 25%RH~80%RH(No condensation) Storage: Temperature: -40~55 C , Humidity: ≤93%RH(40 C , No condensation)
Power requirements	Rated voltage:90~264V Rated frequency range:50~60Hz
Safety marks	GB 4943.1
Certificate	DNV ISO14001, BSI ISO9001, OHSAS 18001
Note	1. The technical specifications in this catalog are the laboratory measurement data which achieved under the national standard for the storage and work environment (room temperature), the specifications of the testing papers are specified in the Users' Manual. 2. The technical specifications are subject to change without notice. 3. All trademarks are the properties of their respective holders.

*The specifications above are subject to be changed without notice.

Jolimark[®]

Address: Unit 01, 23A/F, K.Wah Centre, 191 Java Road, North Point, Hong Kong

Tel: (852) 25582457

Fax: (852) 28979610

Email: sales@kongyue.com.hk

Http://www.jolimark.com/en